

Hi-X50



Professional Closed-Back On-Ear Headphones

Frequency range: 5 Hz - 28 kHz

Sensitivity: 118dBspl/V **THD** (@ 1kHz): < 0.1%

Impedance: 25 Ω

Input Power: 150 mW

Cable (detachable): 3m

Connector: 3.5mm (1/8")

Adapter (included): 3.5mm to 6.3mm (1/8" to 1/4")

Dimensions: $190 \times 170 \times 70 \text{ mm}$

Weight (without cable): 285g

The Hi-X50 supra-aural closed-back headphones provide on-the-ear comfort as well as portability with the foldable hinge design. Metal parts are used for all critical elements in order to guarantee long durability even under rough conditions be it in live or studio situations.

Developed from scratch, the all new 44mm Hi-X driver features a ring magnet system - a home-grown technology which has been incorporated into various award-winning headphones in the past by our engineers. It allows improved air-flow and the strongest magnetic field in its class. This ring magnet structure coupled with a copper-clad aluminum voice coil reduces the weight of the membrane and voice coil that sits on it allowing it to move or change direction faster providing a better impulse reaction, highly desired for contemporary as well as traditional music production.

A double acoustic wall was designed to achieve the best damping results, to support this and increased comfort, the form factor and material of the earpads provide sealing as well as comfort.

Highest attention was paid on construction and materials of the earpads that conbine a secure fit with superior wearing comfort.

Engineered and manufactured in Austria, the Hi-X50, and its over-ear brother the Hi-X55, are tailored to suit the demanding production conditions of today. With the all-digital signal chain, using 24bit or even 32bit, the dynamic depth of contemporary source tracks puts engineer and material at the mixing desk to the test.

All information is correct at time of writing, please check <u>www.austrianaudio.com</u> for updates as specifications can change.







